



AUTOMOTIVE RESTRAINT FITTERS AUSTRALIA

Unit 2-3 Gantry Place, Braemar NSW 2575
PO Box 572 Mittagong NSW 2575
Tel (02) 4872 3903
Fax (02) 4872 1815
Email damien@arfa.com.au
www.automotiverestraints.com.au

ABN 32 131 300 439

NEW OUTBOUND SEAT MOUNTED CHILD RESTRAINT FOR TOYOTA COMMUTER YEARS 2005 ON

Anchorage Fitting Instructions

Fitting Instructions for Child Restraint
Anchorage onto the Single and double
fixed based seats in the outbound
positions only.

TOOLS REQUIRED

- Small Flat Screwdriver
- Phillips head screwdriver (No.2)
- 4mm Alan Key
- Loctite low strength thread locker

FITTING

1. Using small flat screwdriver, carefully open flaps on grab handle to expose screws that hold the handle in place.
2. Using Phillip's head screwdriver remove original screws and handle grip.
3. Place original screws in a marked bag in the glove box, or discard.
4. Place CRA bracket under grab handle with the (v) or curved side facing downwards
5. Use 1 drop of Loctite on each of the (M6 X 35MM socket head cap screws, 12.9 Grade) fit handle and the anchor bracket back onto the seat using 4mm Alan key and (tighten by hand, so as not to force the cap screw through the grab handle).
6. Allows for 3 x A200 RH, AND 2 x A200 LH
7. Made under licence to Vehicle Engineering Australia P/L
8. Test Report: JWW008-CRA-01 Complies with ADR 34/01

Not for Rearmost or Side Fold Up Seats.



WARNING: Child restraint anchorages are designed to withstand only those loads imposed by correctly fitted child restraints. Under no circumstances are they to be used for adult seatbelts or harnesses

WHEN ORDERING ASK FOR EITHER LEFT OR RIGHT HAND BRACKETS THEY ARE NOT INTERCHANGABLE (A200LH) OR (A200RH)

Picture display is A200 RH

Serving the Community - Saving Lives.